

# FOAM BREAKER ULTRA-S

### ANTIFOAMING/DEFOAMING AGENT

#### PRINCIPAL FUNCTIONING AGENTS

Dimethylpolysiloxane..... Methylated Silicon... CONSTITUENTS INEFFECTIVE AS SPRAY ADJUVANT......90%

TOTAL All ingredients are exempt from the requirements of a tolerance as specified in 40 CFR 180.

#### KEEP OUT OF REACH OF CHILDREN WARNING

## CAUSES EYE IRRITATION ALWAYS SHAKE WELL BEFORE USING

PRECAUTIONARY STATEMENTS
Wash hands thoroughly after handling.
STORAGE AND DISPOSAL:

STORAGE AND DISPOSAL:
Store above 40° F. Do not freeze. Store in original container only. Do not contaminate water, food or feed by storage or disposal. Do not reuse empty container. Triple rinse (or equivalent) during mixing and loading. Recycling decontaminated containers is the best option of container disposal. The Agricultural Container Recycling Council (ACRC) operates the national recycling program. Contact your state and local ACRC recycler or visit the ACRC web page at www.acrecycle.org. Decontaminated containers may also be disposed of in a sanitary landfill.

#### FIRST AID

IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention.

For Emergency, Spill, Leak, Fire, Exposure, Or Accident, Call CHEMTREC 1-800-424-9300
Approved for Aquatic Use with Pesticides labeled for

Aquatic Use.

#### **DIRECTIONS FOR USE**

The use of FOAM BREAKER ULTRA-S can control foaming of spray mixtures. The reduction of foam can decrease mixing and filling times and reduce material loss caused by foaming over of spray tanks. It can reduce risks of unwanted and unsightly vegetation kills or contamination caused by foaming over.

For foam reduction when mixing spray solutions, add FOAM BREAKER ULTRA-S at the rate of 1 ounce per 100 gallons of solution. Water hardness. temperature and spray tank mixture may call for more or less. Adjust the rate until the desired control is achieved. Add FOAM BREAKER ULTRA-S to the partly water-filled tank first and agitate well before adding other products to the spray solution.

If foaming should occur after spray mixture is in tank, FOAM BREAKER ULTRA-S can be applied directly to the surface using the trigger sprayer for fast foam knockdown.

Foam Breaker Ultra-S is Manufactured for Aspect Ag, LLC

NET CONTENTS: ONE QUART PER BOTTLE PACKAGED 12 X 1 QUARTS

..100%